

# XTRABOND®150

## RTV SILICONE SEALANT



XtraBond®150 is a one component, permanently flexible, RTV (Room Temperature Vulcanizing) mildew-resistant silicone sealant that is the industry standard. The product's tough chemical resistance makes it a worry-free solution for a wide range of applications.

XtraBond®150 provides excellent adhesion to cultured marble, tile, glass, vinyl, aluminum, and sheet metal without the need for a primer. The product is engineered to cure rapidly when exposed to atmospheric moisture, to form a durable tight bond that contractors and installers count on. A wide range of packaging options provides users with total flexibility in how the product is applied.

### FEATURES

- Approved for Cultured Marble
- Excellent Adhesion to Glass
- Window & Door Approved
- Easy to Gun, Easy to Tool
- Non-Sag & Slump
- Non-Paintable

### APPLICATIONS

- General Construction
- Kitchen & Bath
- Transportation
- Industrial

#### Green Advantage Program

This XtraBond® product is a part of Premier's "Green Advantage" Program – the designation of our commitment to not only superior products & services, but also the environment. Our engineering formulations, manufacturing standards and production practices allow us to be a leader in the supply of eco-friendly and VOC compliant products. Learn more at [www.PremierBuildingSolutions.net/green](http://www.PremierBuildingSolutions.net/green)



#### Weather Defense System

This XtraBond® product is a part of the XtraGuard Weather Defense System™, an integrated product line of building components developed from advanced materials research that increase the durability and comfort of residential and commercial structures by effectively managing moisture. The product's aggressive adhesion and compatibility with all major building materials makes it a critical link in the XtraGuard Weather Defense System, when combined with the company's complete line of Wraps and Flashing Products.



#### Who is Premier?

This XtraBond® product is manufactured and distributed by Premier Building Solutions, a manufacturer of high performance systems that provide protection in commercial and residential buildings – as well as a variety of other industrial and transportation applications.

The company's history of innovation has led to the development of breakthrough adhesive chemistries and new industrial-strength products that help customers increase the efficiency and durability of their critical assets.



PREMIER BUILDING SOLUTIONS, INC  
866-512-GLUE (4583) • Massillon, OH  
[www.PremierBuildingSolutions.net](http://www.PremierBuildingSolutions.net)





# XTRABOND®150

## RTV SILICONE SEALANT

### PROPERTIES:

Skin Time .....	12 Minutes
Tack Free Time .....	20 Minutes
Cure Rate .....	1/4" Bead per 24 Hrs
VOC .....	9 g/L (0.14%)
Elongation @ Break .....	300% - 400%
Shore A .....	20 +/- 5
Movement Capability .....	25%
UV Rating .....	No discoloration or change in appearance after 12 months of UV
Lap Shear .....	190 psi
Tensile Strength .....	80 psi
Staining .....	None
Low Temp. Flexibility .....	Retained to -90 deg. F.
High Temp. Flexibility .....	Up to 425 deg. F for short periods
Sag .....	None

**SPECIFICATIONS:** XtraBond®150 meets or exceeds ASTM C920, Type S, Grade NS, Class 25, Use NT, M, G, A, O; TT-S-00230C & TT-S-001534A (COM-NBS).

**COLORS:** This product is offered in hundreds of colors using our Custom Color Matching & Mixing System. For current color offerings, please visit our website: [www.premierbuildingsolutions.net/color/](http://www.premierbuildingsolutions.net/color/)

**SURFACE PREPARATIONS:** The substrate must be clean, frost free and free of any oils, greases or incompatible sealers that may interfere with adhesion. Do not apply if surface is contaminated. It is recommended to test all substrates prior to applications.

**DIRECTIONS:** For best results, prepare clean surface. Cut nozzle to desired bead size. Apply with caulking gun, forcing sealant onto the substrate, then tool if needed. Clean excess material with mineral spirits or similar solvent.

**STORAGE:** Material is to be stored under controlled dry environment (below 75° F). Use within 18 months from date of manufacture. For best results, keep material in tightly closed containers when not in use.

**LIMITED LIFETIME WARRANTY:** This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Building Solutions, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

*Premier Building Solutions specifically disclaims and makes no warranties, express or implied, about this product, its merchantability, or its fitness for a particular purpose. All recommendations, directions, and suggestions for its use are consistent with our testing and research for a variety of applications, but no promises, guarantees, or warranties are being made with regard to its use, whether or not consistent with the directions, or its effectiveness for any given application. Users of this product should do so in compliance with all applicable laws and regulations. User of this product should conduct its own field test, to assure results.*

## PACKAGING



CARTRIDGES



PAILS



55GAL DRUMS