

XTRABOND®9500SL

SELF-LEVELING ADVANCED POLYMER SEALANT



XtraBond®9500SL is a high performance, one component advanced polymer sealant that is self-leveling and permanently flexible. The product's advanced chemistry delivers a fast-curing solution – across a wide range of temperatures – that is ideal for horizontal construction and industrial applications where self-leveling is critical to the finished product.

XtraBond®9500SL contains no solvents and very low volatile organic compounds (VOCs,) so it is easy on the environment and installers. The product can be painted in as little as 2 hours.

FEATURES

- Fast Cure at a Wide Range of Temperatures
- Paintable in 2 hours
- Very Low VOCs
- Self-Leveling
- No Solvents

APPLICATIONS

- Concrete Expansion Joints & Cracks
- Horizontal Joints
- Roof Joint Seals
- Transportation
- Industrial

Green Advantage Program

This XtraBond® product is a part of Premier's "Green Advantage" Program – the designation of our commitment to not only superior products & services, but also the environment. Our engineering formulations, manufacturing standards and production practices allow us to be a leader in the supply of eco-friendly and VOC compliant products. Learn more at www.PremierBuildingSolutions.net/green



Weather Defense System

This XtraBond® product is a part of the XtraGuard Weather Defense System™, an integrated product line of building components developed from advanced materials research that increase the durability and comfort of residential and commercial structures by effectively managing moisture. The product's aggressive adhesion and compatibility with all major building materials makes it a critical link in the XtraGuard Weather Defense System, when combined with the company's complete line of Wraps and Flashing Products.



Who is Premier?

This XtraBond® product is manufactured and distributed by Premier Building Solutions, a manufacturer of high performance systems that provide protection in commercial and residential buildings – as well as a variety of other industrial and transportation applications.

The company's history of innovation has led to the development of breakthrough adhesive chemistries and new industrial-strength products that help customers increase the efficiency and durability of their critical assets.



XTRABOND®9500SL

SELF-LEVELING ADVANCED POLYMER SEALANT


PROPERTIES:

Skin Time	Less than 20 minutes @ 77 degF/ 50% RH
Tack Free Time	Less than 1 hour @ 77 degF / 50% RH
Cure Rate	1/4" Bead per 24 Hrs
VOC	9 g/L (0.0751 lb/gal)
Elongation @ Break	450%
Shore A	35 +- 5
Movement Capability %	25%
UV Rating	No discoloration or change in appearance after 2500 hours of UV
Lap Shear	325 psi
Tensile Strength	250 psi
Staining	None
Low Temp. Flexibility	Retained to -90 degrees
High Temp. Flexibility	Up to 425 deg. F for short periods

SPECIFICATIONS: XtraBond®9500SL meets or exceeds the requirements of ASTM C920 Type S Grade P Class 25, Use T and M. CAN/CGSB-19.13-M87 Class 1-40-B-N & C-1-25-B-N. Federal Specification TT-S-00230C Type I Class A.

COLORS: This product is offered in a wide range of colors using our Custom Color Matching & Mixing System. For current color offerings, please visit our website at www.premierbuildingsolutions.net

SURFACE PREPARATIONS: The substrate must be clean, frost free and free of any oils, greases or incompatible sealers that may interfere with adhesion. Do not apply if surface is contaminated. It is recommended to test all substrates prior to applications.

DIRECTIONS: For best results, prepare clean surface. Cut nozzle to desired bead size. Apply with caulking gun, forcing sealant onto the substrate, then tool if needed. Clean excess material with mineral spirits or similar solvent.

STORAGE: Material is to be stored under controlled dry environment (below 75° F). Use within 10 months from date of manufacture.

LIMITED LIFETIME WARRANTY: This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Building Solutions, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

Premier Building Solutions specifically disclaims and makes no warranties, express or implied, about this product, its merchantability, or its fitness for a particular purpose. All recommendations, directions, and suggestions for its use are consistent with our testing and research for a variety of applications, but no promises, guarantees, or warranties are being made with regard to its use, whether or not consistent with the directions, or its effectiveness for any given application. Users of this product should do so in compliance with all applicable laws and regulations. User of this product should conduct its own field test, to assure results.

PACKAGING



CARTRIDGES



PAILS



55GAL DRUMS