

XTRABOND®9500TX

TEXTURED ADVANCED POLYMER SEALANT



XtraBond®9500TX is a textured high performance, one component, permanently flexible advanced polymer sealant that's easy to install. Its advanced chemistry makes it ideal for a wide range of construction and industrial applications.

XtraBond®9500TX cures quickly when exposed to atmospheric moisture across a wide range of temperatures, so it is easy to use. The product's aggressive adhesion to common construction substrates and compatibility with rubberized flashing makes it a logical choice for construction professionals. Its textured appearance makes it easy to blend into the surrounding surfaces.

FEATURES

- Fast Cure at a Wide Range of Temperatures
- Compatible with SBS Flashing
- Textured Appearance
- Paintable in 2 Hours
- Very Low VOCs
- No Solvents

APPLICATIONS

- Perimeter sealing of windows, doors & skylights
- Waterproof Membrane
- Industrial
- Stucco
- Siding

Green Advantage Program

This XtraBond® product is a part of Premier's "Green Advantage" Program – the designation of our commitment to not only superior products & services, but also the environment. Our engineering formulations, manufacturing standards and production practices allow us to be a leader in the supply of eco-friendly and VOC compliant products. Learn more at www.PremierBuildingSolutions.net/green



Weather Defense System

This XtraBond® product is a part of the XtraGuard Weather Defense System™, an integrated product line of building components developed from advanced materials research that increase the durability and comfort of residential and commercial structures by effectively managing moisture. The product's aggressive adhesion and compatibility with all major building materials makes it a critical link in the XtraGuard Weather Defense System, when combined with the company's complete line of Wraps and Flashing Products.



Who is Premier?

This XtraBond® product is manufactured and distributed by Premier Building Solutions, a manufacturer of high performance systems that provide protection in commercial and residential buildings – as well as a variety of other industrial and transportation applications.

The company's history of innovation has led to the development of breakthrough adhesive chemistries and new industrial-strength products that help customers increase the efficiency and durability of their critical assets.



PREMIER BUILDING SOLUTIONS, INC
866-512-GLUE (4583) • Massillon, OH
www.PremierBuildingSolutions.net



XTRABOND®9500TX

TEXTURED ADVANCED POLYMER SEALANT


PROPERTIES:

Skin Time	Less than 1.5 Hours @77 F/ 50% RH
Tack Free Time	Less than 4 hours @77 F / 50% RH
Cure Rate	1/4 " Bead / 24 Hours
VOC	3.59%
Elongation @ Break	525%
Shore A	30 +- 5
Movement Capability %	25%
Peel Strength	30 psi
Lap Shear	325 psi
Tensile Strength	250 psi
Staining	None
Service Temperature	185 deg. F

SPECIFICATIONS: XtraBond@9500TX meets or exceeds the requirements of ASTM C 920, Type S, Grade NS, Class 25, Use NT, M, G and A • Federal Specification TT-S-00230C, Type II, Class A • CAN/CGSB-19 13-M87 • AAMA 808.3-92 Exterior Perimeter Sealing.

COLORS: This product is offered in a wide range of colors using our Custom Color Matching & Mixing System. For current color offerings, please visit our website at www.premierbuildingsolutions.net

SURFACE PREPARATIONS: The substrate must be clean, frost free and free of any oils, greases or incompatible sealers that may interfere with adhesion. Do not apply if surface is contaminated. It is recommended to test all substrates prior to applications.

DIRECTIONS: For Best Results, prepare clean, dry surface. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed. Can be applied in a wide range of temperatures. Clean excess material with mineral spirits or similar solvent.

STORAGE: Material is to be stored under controlled dry environment (below 75° F). Use within 10 months from date of manufacture.

LIMITED LIFETIME WARRANTY: This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Building Solutions, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

Premier Building Solutions specifically disclaims and makes no warranties, express or implied, about this product, its merchantability, or its fitness for a particular purpose. All recommendations, directions, and suggestions for its use are consistent with our testing and research for a variety of applications, but no promises, guarantees, or warranties are being made with regard to its use, whether or not consistent with the directions, or its effectiveness for any given application. Users of this product should do so in compliance with all applicable laws and regulations. User of this product should conduct its own field test, to assure results.

PACKAGING



CARTRIDGES



SAUSAGES



PAILS



55GAL DRUMS