

XTRABOND®9500UC

ULTRA-CLEAR ADVANCED POLYMER SEALANT



XtraBond®9500UC is a high performance, multi-purpose advanced polymer sealant that is completely clear. The product is engineered to deliver aggressive adhesion with the most common construction substrates across a wide range of temperatures.

XtraBond®9500UC contains no solvents and very low volatile organic compounds (VOCs,) so it is easy on the environment. It is the ideal choice for industrial applications where an aggressive, durable bond is required, yet the sealant needs to be undetectable.

FEATURES

- Aggressive Adhesion to Common Construction Substrates
- Advanced Ultra Clear Formula
- Extrudes at Zero Degrees
- Very Low VOCs
- No Solvents

APPLICATIONS

- Perimeter sealing of windows, doors & skylights
- Sheet Metal
- Industrial

Green Advantage Program

This XtraBond® product is a part of Premier's "Green Advantage" Program – the designation of our commitment to not only superior products & services, but also the environment. Our engineering formulations, manufacturing standards and production practices allow us to be a leader in the supply of eco-friendly and VOC compliant products. Learn more at www.PremierBuildingSolutions.net/green



Weather Defense System

This XtraBond® product is a part of the XtraGuard Weather Defense System™, an integrated product line of building components developed from advanced materials research that increase the durability and comfort of residential and commercial structures by effectively managing moisture. The product's aggressive adhesion and compatibility with all major building materials makes it a critical link in the XtraGuard Weather Defense System, when combined with the company's complete line of Wraps and Flashing Products.



Who is Premier?

This XtraBond® product is manufactured and distributed by Premier Building Solutions, a manufacturer of high performance systems that provide protection in commercial and residential buildings – as well as a variety of other industrial and transportation applications.

The company's history of innovation has led to the development of breakthrough adhesive chemistries and new industrial-strength products that help customers increase the efficiency and durability of their critical assets.



PREMIER BUILDING SOLUTIONS, INC
866-512-GLUE (4583) • Massillon, OH
www.PremierBuildingSolutions.net



XTRABOND®9500UC

ULTRA-CLEAR ADVANCED POLYMER SEALANT

PROPERTIES:

Skin Time	Less than 20 minutes @ 77 degF/ 50% RH
Tack Free Time	Less than 1 hour @ 77 degF / 50% RH
Cure Rate	1/4" Bead per 24 Hrs
VOC	9 g/L (0.0751 lb/gal)
Elongation @ Break	450% - 500%
Shore A	30
Movement Capability %	25%
UV Rating	No discoloration or change in appearance after 12 months of UV
Lap Shear	325 psi
Tensile Strength	250 psi
Staining	None
Low Temp. Flexibility	Retained to -90 degrees
High Temp. Flexibility	Up to 425 F for short periods
Sag	None

SPECIFICATIONS: XtraBond®9500UC conforms to the requirements of ASTM C-920 Type S & TTS-0230C, Grade NT, Class 25.

COLORS: Ultra Clear

SURFACE PREPARATIONS: The substrate must be clean, frost free and free of any oils, greases or incompatible sealers that may interfere with adhesion. Do not apply if surface is contaminated. It is recommended to test all substrates prior to applications.

DIRECTIONS: For best Results, prepare clean, dry surface. Cut nozzle to desired bead size. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed. Clean excess material with mineral spirits or similar solvent.

STORAGE: Material is to be stored under controlled dry environment (below 75° F). Use within 10 months from date of manufacture.

PACKAGING



CARTRIDGES



PAILS



55GAL DRUMS

LIMITED LIFETIME WARRANTY: This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Building Solutions, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

Premier Building Solutions specifically disclaims and makes no warranties, express or implied, about this product, its merchantability, or its fitness for a particular purpose. All recommendations, directions, and suggestions for its use are consistent with our testing and research for a variety of applications, but no promises, guarantees, or warranties are being made with regard to its use, whether or not consistent with the directions, or its effectiveness for any given application. Users of this product should do so in compliance with all applicable laws and regulations. User of this product should conduct its own field test, to assure results.

131120-PBS-XB9500UC-Ver3