

XTRAFoam™HH

HAND-HELD ADHESIVE FOAM



XtraFoam™HH is a very low expansion, one-component, multipurpose, polyurethane foam formulated to seal around window and door frames. Packaged in a hand-held can, the product's low pressure, airtight insulation foam blocks drafts, moisture and insects without distending window and door frames. Once applied, it doesn't shrink or expand.

XtraFoam™'s advanced chemistry ensures excellent adhesion to most substrates, and an excellent water-resistant, airtight seal – as well as outstanding thermal and acoustical insulation. The product contains no CFC's or HCFC's, so it is environmentally friendly.

FEATURES

- Excellent Stability (no shrink or post expansion)
- Excellent Adhesion to Various Substrates
- High Thermal and Acoustical Resistance
- Provides Water-Resistant, Airtight Seal
- Exceptional Filling Capacities
- Low Expansion Formula
- Hand-Held Can

APPLICATIONS

- Areas of Air Infiltration
- Windows & Doors
- Electrical Panels
- Insulation
- Pipes

Green Advantage Program

This XtraBond® product is a part of Premier's "Green Advantage" Program – the designation of our commitment to not only superior products & services, but also the environment. Our engineering formulations, manufacturing standards and production practices allow us to be a leader in the supply of eco-friendly and VOC compliant products. Learn more at www.PremierBuildingSolutions.net/green



Weather Defense System

This XtraBond® product is a part of the XtraGuard Weather Defense System™, an integrated product line of building components developed from advanced materials research that increase the durability and comfort of residential and commercial structures by effectively managing moisture. The product's aggressive adhesion and compatibility with all major building materials makes it a critical link in the XtraGuard Weather Defense System, when combined with the company's complete line of Wraps and Flashing Products.



Who is Premier?

This XtraBond® product is manufactured and distributed by Premier Building Solutions, a manufacturer of high performance systems that provide protection in commercial and residential buildings – as well as a variety of other industrial and transportation applications.

The company's history of innovation has led to the development of breakthrough adhesive chemistries and new industrial-strength products that help customers increase the efficiency and durability of their critical assets.



PREMIER BUILDING SOLUTIONS, INC
866-512-GLUE (4583) • Massillon, OH
www.PremierBuildingSolutions.net



XTRAFoam™ HH

HAND-HELD ADHESIVE FOAM



PROPERTIES:

- BasePolyurethane
- Curing SystemMoisture Cure
- Core Density1.25 -1.70 lbs./ cu.ft.
- R-Value ASTM C5184.25 per inch
- Pressure Build0.15-1.20 psi
- ColorYellow
- Service Temp230 Degrees F
- Curing Rate30 Minutes for a ½ bead
- Take Free5-10 minutes for a ½ bead
- Shelf Life12 months, from date of mfg.

Usage:

	LINEAR FEET									
	500	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	5,000
1/4" (6.3 mm)	1	1	1	1	2	2	2	2	3	4
3/8" (9.5 mm)	1	2	2	3	4	4	5	6	6	7
1/2" (12.7 mm)	2	3	4	5	6	7	8	10	11	12
	152	305	457	610	762	914	1067	1219	1372	1524
LINEAR METERS										

APPLICATION: Type: ALL substrates except PE and PP. State of Surface: clean, free of dust and grease. Preparation: Moistening of the surfaces improves adhesion, curing, and denser cellular structure. For best results, use in temperatures between 60-100°F. For better results, spray mist into cavity prior to applying foam.

STORAGE: Material must be stored upright when not in use.

SHELF-LIFE: 12 months in unopened packaging in a cool and dry storage place at temperatures of 75°F.


HEALTH AND SAFETY RECOMMENDATION: Apply the standard industrial hygiene techniques. Wear gloves and safety goggles. Remove cured foam by mechanical means only, never burn away. SEE INDIVIDUAL CANS OF FOAM FOR SPECIFIC INSTRUCTIONS.

PACKAGING



AEROSOL CANS

CLASSIFIED



R19028 - CAULKING AND SEALANTS
SURFACE BURNING CHARACTERISTICS
APPLIED TO INORGANIC REINFORCED
CEMENT BOARD*
FLAME SPREAD: 15
SMOKE DEVELOPED: 19HU

*Tested as applied in two 1 inch beads, 8 inches on center
covering 11.1% of the exposed test sample area.

DOT 2Q

LIMITED LIFETIME WARRANTY: This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Building Solutions, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

Premier Building Solutions specifically disclaims and makes no warranties, express or implied, about this product, its merchantability, or its fitness for a particular purpose. All recommendations, directions, and suggestions for its use are consistent with our testing and research for a variety of applications, but no promises, guarantees, or warranties are being made with regard to its use, whether or not consistent with the directions, or its effectiveness for any given application. Users of this product should do so in compliance with all applicable laws and regulations. User of this product should conduct its own field test, to assure results.

131120-PBS-XtraFoamHH-Ver3